



## Tipper Semi-Trailer 42 M<sup>3</sup>

### Specifications

<b>Tipper Box Volume</b>	42 m <sup>3</sup>
<b>Length</b>	9400mm + 350mm
<b>Width</b>	2700mm
<b>Height</b>	1610mm
<b>Deck Plate Thickness</b>	8mm
<b>Thickness of Side Plate</b>	6mm
<b>Thickness of Front Plate</b>	6mm
<b>Thickness of Tail Gate (Automatically Open Type)</b>	6mm
<b>Chassis</b>	Made out of two strong beams
<b>Axles</b>	3x16000 Kgs.-BPW or VT (Upon availability)
<b>King Pin Size</b>	3½ inches Dia. (Jost)
<b>Landing Gear</b>	Heavy-duty Two Speed Telescopic. Type
<b>Hydraulic Jack</b>	'HYVA'/'PENTA' – Hyd. Jack. (Upon availability) 90 Ton Capacity (Without Wet Kit.)
<b>Tyres</b>	1200 R24" – Bridgestone/Goodyear/Pirelli Upon availability (12 Nos.)
<b>Rim Size</b>	8.5x24"
<b>Brake System</b>	Two Line Air Brakes (Wabco.)
<b>Accessories</b>	Toolbox, Twin Spare Tyre Carrier, Rear Mudguard with Mudflaps, Side Lights and Rear Bumper
<b>Painting</b>	All steels grit blasted, coated with Red-oxide Primer and painted with two coats final enamel paint of customer's choice of colour